



DASIC INTERNATIONAL LTD

SUPER V-KLEEN

Non-hazardous, super concentrated, fast acting forecourt cleaner

Super V-Kleen is a new advanced water based biodegradable formulation incorporating a new surfactant system for faster cleaning.

Super V-Kleen has been manufactured to give the most effective answer to cleaning problems on petrol and diesel pumps, road vehicles, workshop floors, walls, canopies, metal surfaces, concrete and brickwork.

- **Environmentally friendly**
- **Does not interfere with interceptors**
- **Not classifiable as hazardous under CHIP Regulations**
- **Safe, fast and easy to use**
- **Concentrated formulation**
- **Multi-purpose cleaner**
- **Non-caustic**
- **Non-acidic**
- **Solvent free and non-flammable**
- **Biodegradable surfactants**

DIRECTIONS FOR USE

Petrol and Diesel Pumps:

For use on pumps and fuel line couplings and nozzles. Dilute **Super V-Kleen** at the rate of 1 part to 20-30 parts water. Simply apply by spray or cloth and then wipe off.

Road vehicles:

For manual cleaning, use at a dilution rate of 1 part **Super V-Kleen** to 100 parts water. Apply by mop or brush, starting from the bottom upwards. Rinse thoroughly with water.

For application through hot or cold pressure wash machines use at rate of 1%, applying from the bottom upwards. For heavily soiled commercial vehicle chassis, higher concentrations (up to 5%) may be necessary. Rinse off with high pressure.

Continued . . .

Dasic International Ltd
Winchester Hill, Romsey,
Hampshire, SO51 7YD, UK
Tel: +44 (0) 1794 512419
Fax: +44 (0) 1794 522346
Email: info@dasicinter.com
Web: www.dasicinter.com

The information contained in this publication is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or is to be implied in respect of such information or in respect of any recommendations or suggestions which may be made or that any use will not infringe any patent.



BS EN ISO 9001
Certificate No.1899

Concrete and Brickwork:

Dilute **Super V-Kleen** at the rate of 1 part to 9 parts water, depending on the degree of soiling present. It may be applied by either pouring the solution on to the soiled area or by pressure sprayer. Scrub over the area with a stiff broom and allow to stand for up to 10 minutes. Then rinse away.

Workshop Floors, Walls, Canopies and Metal Surfaces:

Dilute **Super V-Kleen** at the rate of 1 part to 20-30 parts water. Simply apply by spray, cloth or mop

DASIC SUPER V-KLEEN SHOULD NOT BE USED NEAT. IT WILL NOT PERFORM PROPERLY WITHOUT WATER.

PACKAGING

4 x 5 litres, 25 litres, 200 litres and bulk.

HEALTH AND SAFETY INSTRUCTIONS

Always consult the product label and Dasic Safety Data Sheet before use.

Dasic International Ltd
Winchester Hill, Romsey,
Hampshire, SO51 7YD, UK
Tel: +44 (0) 1794 512419
Fax: +44 (0) 1794 522346
Email: info@dasicinter.com
Web: www.dasicinter.com

The information contained in this publication is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or is to be implied in respect of such information or in respect of any recommendations or suggestions which may be made or that any use will not infringe any patent.



BS EN ISO 001
Certificate no.1899